

RELIABLE ULTRASONIC MEASUREMENT

CYGNUS MINI ROV MOUNTABLE ULTRASONIC THICKNESS GAUGE



The Cygnus Mini ROV Mountable thickness gauge has been specially designed to be mounted onto small observation ROVs with or without a manipulator facility. Built in conjunction with VideoRay, this subsea thickness gauge will allow the operator to carry out an ultrasonic thickness measurement in areas that have previously been unfeasible using larger ROVs or divers. And no need to remove coatings!



HULL UTM NSPECTION CIVIL ENGINEERII MARINE STRUCTURES

OFFSHORE PLATFORMS

...UWILD or IWS class surveys, subsea inspection, repair and maintenance (IRM) of infrastructure, underwater equipment

/ideoHa

IDEAL FOR

USE IN





CYGNUS MINI ROV MOUNTABLE **KEY FEATURES**





- Supplied with CygLink software to display and process measurements on a computer at the surface
- Easy calibration at the surface via CygLink software or Topside Repeater (TSR) unit
- Optional Topside Repeater (TSR) unit allowing readings to be displayed remotely and superimposed onto ROV's camera screen
- Optional purpose-built ROV probe handlers for optimal alignment



Cygnus S1

Cyglink Computer Software

Cygnus G1

CygLink is a Windows[®] application that allows remote viewing, control and data logging of the Mini ROV gauge. The software can generate survey reports in PDF or export to a CSV file. Designed for Windows® 7 and above.



OPTIONS AND ACCESSORIES

Engineered Probe Handling Solutions

Topside Repeater Remote Display Unit

Topside Repeater with Video Overlay

SO TO PRODUCT PAGE



TOPSIDE PURPOSE-CYGLINK SOFTWARE REPEATER OPTION

BUILT PROBE HANDLERS OPTION

Visit www.cygnus-instruments.com to explore our full product range

Call our team today on +44 (0) 1305 265 533 for expert product advice

CYGNUS MINI ROV MOUNTABLE SPECIFICATION

Feature	Description
Materials	Velocities between 1000 m/s and 9995 m/s (0.0400 and 0.3998 in/microsec)
Measurement Range in Steel	1mm - 250mm (0.040" - 10.000") depending on selected probe and configuration, material and temperature
Accuracy	±0.1mm (±0.004") or 0.1% of thickness measurement, whichever is greatest, when calibrated in accordance with Cygnus Instruments calibration procedure
Resolution	0.1 mm or 0.05 mm (selectable) (0.005" or 0.002")
Probe Options	Single crystal probes
Power	7.5 - 30 V DC @ 150 mA (max)
Display	PC or laptop with VGA (not included)
Size	160mm x 62mm (6.3 x 2.4 in.)
Weight in Air	550g (19.4 oz)
Operating Temp.	-10°C to +50°C (14°F to 122°F)
Approvals	RINA Type approved
Testing	Tested to 500m (1,640ft) depth
Communication	RS-422, Simplex Single Pair or 2400 Baud (RS-232 9600 Baud output available as special order)
Standards	Designed for EN 15317
Compliance	CE, UKCA, RoHS
Warranty	3 years on gauge and 6 months on probe







Cygnus Headquarters

Cygnus UAE

Cygnus USA

Cygnus Singapore

Call +65 6252 5909